

PRODUCT DATA SHEET

2025-02-13



Article number:

4712678331GG

Braked castor 125 mm, total stop brake, TPE-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Zinc brake. Riveted wheel axle. Wheel with grey TPE-tyre. Hub made of grey PP with threadguards. Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	125 mm
Totalt height	159 mm
Load Capacity (dynamic)	100 kg
Castor model	Brake
Fitting	Top plate
Material Tread	TPE
Bearing	Ball bearing
Plate Size	77x67 mm
CC Distance	59x49 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	32 mm
Material Hub	Polypropylen (pp)
Top Hole	12x8,5 mm
Color Tread	Grey
Material Type	RoHS (EU) - Approved
Teststandard	EN 12530
Offset	39 mm
Material Thickness Bracket	2,5 mm
Swivel radius	128 mm
Product Weight	0,82 kg
Temperature Range	-20°C to +50°C

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.