

PRODUCT DATA SHEET

2024-02-13



Article number:

58166854320ZB-ALU

Braked castor 160 mm, total stop brake, elastic convex PU-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with orange elastic convex PU-tyre. Hub made of aluminum. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	160 mm
Totalt height	195 mm
Load Capacity (dynamic)	350 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Elastic Polyurethan
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	93° Shore A
Brake	Total brake
Width of tread	50 mm
Material Hub	Aluminium
Top Hole	11x14 mm
Dyn. Load Capacity (4km/)	350 kg
Color Tread	Brown
Material Type	RoHS (EU) - Approved
Offset	55 mm
Material Thickness Bracket	3 mm
Materialthickplate	4 mm
Swivel radius	159 mm
Product Weight	2.91 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.