

PRODUCT DATA SHEET

2024-02-05



Article number:

5A12665322SS


Braked castor 125 mm, total stop brake, rubber-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with black rubber-tyre. Hub made of PP. Roller bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	125 mm
Totalt height	155 mm
Load Capacity (dynamic)	100 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Rubber
Bearing	Roller bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	38 mm
Material Hub	Polypropylen (pp)
Top Hole	9 mm
Fork Width	46 mm
Dyn. Load Capacity (4km/)	100 kg
Color Tread	Black
Material Type	RoHS (EU) - Approved
Offset	44 mm
Material Thickness Bracket	2,5 mm
Materialthicknessplate	2,5 mm
Product Weight	1,26 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.