

PRODUCT DATA SHEET

2024-02-09



Article number:

5220685322SS

Braked castor 200 mm, total stop brake, rubber-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with black rubber-tyre. Hub made of PP. Roller bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	200 mm
Totalt height	235 mm
Load Capacity (dynamic)	205 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Rubber
Bearing	Roller bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	50 mm
Material Hub	Polypropylen (pp)
Top Hole	11x18 mm
Color Tread	Black
Material Type	RoHS (EU) - NOT Approved
Teststandard	EN 12532
Offset	51 mm
Material Thickness Bracket	2.5 mm
Materialthickplate	2.5 mm
Swivel radius	189 mm
Product Weight	2.88 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.