

PRODUCT DATA SHEET

2024-02-06



Article number:

8012007332GGJ

Swivel castor 125 mm, directional lock, TPE-tyre

Swivel bracket with directional lock. Injection moulded plastic bracket in grey PA6-GF35 with ball bearings in the swivel head. Center hole fitting. Wheel axle with nut. Wheel with grey TPE-tyre. Hub made of grey PP with threadguards. Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	125 mm
Totalt height	160 mm
Load Capacity (dynamic)	100 kg
Castor model	Swivel
Fitting	Centre hole
Material Tread	TPE
Bearing	Ball bearing
Thread hardness (Shore°)	85° Shore A
Centre Bolt Hole	10.2 mm
Brake	Directional lock
Width of tread	32 mm
Material Hub	Polypropylen (pp)
Wheel Pattern	EN 12530
Static Load Capacity	200 kg
Color Tread	Gray RAL 7012
Material Type	RoHS (EU) - Approved
Teststandard	EN 12530
Offset	44 mm
Ball bearing	6202-ZZ
Swivel radius	107 mm
Product Weight	0.49 kg
Temperature Range	-20°C to +50°C

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.