

# PRODUCT DATA SHEET

2024-04-08



Article number:

5810005933GS


Braked castor 100 mm, total stop brake, elastic rubber-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting for M12 screw. Wheel axle with nut. Wheel with grey elastic rubber-tyre. Hub made of black Nylon/PA6 with threadguards. Ball bearing.



Image may differ from the actual product.\*

## DIMENSIONS



## SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	225 kg
Castor model	Brake
Fitting	Centre hole
Material Tread	Elastic Rubber
Bearing	Ball bearing
Thread hardness (Shore°)	75° Shore A
Centre Bolt Hole	12.4 mm
Brake	Total brake
Width of tread	36 mm
Material Hub	Nylon PA6
Color Tread	Grey
Material Type	RoHS (EU) - Approved
Teststandard	EN 12532
Offset	41 mm
Material Thickness Bracket	2,5 mm
Swivel radius	129 mm
Product Weight	1 kg
Temperature Range	-30°C to +70°C

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.